


# Type TSF2 H<sub>2</sub> and TSF4 H<sub>2</sub>

## Filter for the fueling station and for vehicles

Dirt particles in the hydrogen fuel may cause damage to the sealing components whilst refuelling. The WEH-Filters are designed to capture dirt and gas-borne debris thereby reducing the danger of erosion.

Type **TSF4-SPECIAL** has been designed for use in hydrogen buses. The filter can be removed for cleaning purposes without disconnecting the media lines.



Type TSF4-SPECIAL



Type TSF4 H<sub>2</sub>

### Technical Data:

**Pressure ranges:**  
350 bar, settled pressure at an uniform gas temperature of 15 °C.  
PN = 350 bar  
PS = 450 bar  
PT = 675 bar

**Temperature range:**  
-40°C up to +85°C

**Registration:**  
PED 97/23/EC: CE 0036

**Design:**  
All parts corrosion-resistant steel; brass. Seals hydrogen compatible.

### Ordering:

**Manufacturer:**  
**WEH GmbH**  
**Gas Technology**  
Siemensstraße 5  
89257 Illertissen  
Germany  
Phone: +49 7303 95190-0  
Fax: +49 7303 95190-9999  
Email: sales@weh.com  
http://www.weh.com

Description	Inlet A* / B* (mm)	Part No.
TSF2	Tube Ø 3/8	C1-18487
TSF4	Tube Ø 12	C1-30214
TSF4	Tube Ø 16	C1-30213
TSF4-SPECIAL	Tube Ø 16	C1-47886

\* Twin ferrule fitting unless other wise specified!

© All rights reserved, WEH GmbH 2009. Any unauthorized use is strictly forbidden. Subject to alteration. No liability will be assumed for any content. Herewith previous versions are no longer valid.